

APPENDIX E

HOLDEN BEACH WORK PLAN



The Town of Holden Beach

Incorporated 1969

110 Rothschild Street
Holden Beach, North Carolina 28462

Phone: 910.842.6488
Fax: 910.842.9315

Mr. Mickey Sugg
Project Manager
US Army Corps of Engineers
69 Darlington Avenue
Wilmington NC 28403-1343

RE: Initiation of NEPA permitting process for Holden Beach Terminal Groin Project

Dear Mr. Sugg,

The Town of Holden Beach would like to continue the permitting process for a terminal groin and beach fill project. Pursuant to our inter-agency scoping meeting on October 12, 2011, you have requested a Work Plan in order to establish a project description and general outline of the tasks to be performed under the National Environmental Policy Act (NEPA) permitting process. By copy of this letter, we would like to initiate the NEPA permitting process for the proposed project.

Please find the attached Work Plan which outlines the general project description (i.e. groin and nourishment) as well as tasks to be conducted during Environmental Impact Statement (EIS) document development. Thank you for your time and we look forward to working with you. Please contact me or our designated coastal engineering firm, Applied Technology and Management, for more information.

Sincerely,

David Hewett
Holden Beach Town Manager

Work Plan for the Proposed Terminal Groin on the East End of Holden Beach

Lockwoods Folly Inlet, North Carolina



November 2, 2011

Prepared for: USACE

Submitted by: The Town of Holden Beach, NC


TABLE OF CONTENTS

1.0	INTRODUCTION.....	1-1
2.0	PURPOSE AND NEED	2-1
3.0	INDEPENDENT BEACH MANAGEMENT ACTIVITIES.....	3-1
3.1	Existing Town Beach Nourishment Permit	3-1
3.2	Island-Wide Nourishment utilizing Offshore Borrow Area	3-1
3.3	USACE 50 Year Project	3-3
4.0	PROJECT SITE HISTORY	4-1
5.0	EXISTING CONDITIONS.....	5-1
5.1	Gross versus Net Sediment Transport	5-5
5.2	Natural Resources.....	5-5
5.3	Economics	5-8
5.3.1	Recreation	5-8
5.3.2	Infrastructure	5-9
5.3.3	Dredging.....	5-10
6.0	AVAILABLE ALTERNATIVES.....	6-1
6.1	No Action	6-1
6.2	Threatened Structure Relocation.....	6-1
6.3	Beach nourishment without inlet relocation	6-2
6.4	Beach nourishment with inlet relocation	6-2
6.5	Sand borrow site analysis/selection	6-3
6.5.1	Turkey Trap Road (Permitted).....	6-6
6.5.2	Smith Borrow Site (Permitted).....	6-6
6.5.3	Tripp Upland Site.....	6-7
6.5.4	Monks Island	6-8


6.5.5	Sheep Island	6-9
6.6	Terminal Groin And Beach nourishment	6-10
7.0	PENDING PREFERRED ALTERNATIVE -TERMINAL GROIN & NOURISHMENT	7-1
7.1	TERMINAL GROIN COMPONENT	7-1
7.2	BEACH FILL COMPONENT	7-3
7.3	CONSTRUCTION METHODS.....	7-6
8.0	EXISTING AND PROPOSED DATA NEEDS AND STUDIES	8-1
8.1	Project Timing.....	8-1
9.0	SUMMARY	9-1
10.0	REFERENCES.....	10-1

This document represents the Work Plan requested by Mr. Mickey Sugg of the US Army Corps of Engineers (USACE) to begin the National Environmental Policy Act (NEPA) permitting process for a terminal groin on the east end of Holden Beach, adjacent to Lockwoods Folly Inlet (see Figure 1-1 for location map). The Work Plan described herein includes the general tasks to be conducted during the NEPA and Environmental Impact Statement (EIS) development process.

The proposed terminal groin is one component of the Town of Holden Beach's ongoing comprehensive beach management program, further described in the Holden Beach 2009 Beach Management Plan. A terminal groin structure on the eastern end of Holden Beach is an alternative that is being considered as the preferred method to reduce the high erosion losses that have historically occurred at the east end of Holden Beach, in addition to proactive sand management of Lockwoods Folly Inlet.




1-1




2011 Long-Term Average Annual Erosion Rate Update at Holden Beach, North Carolina

Legend

2011 Setback Factors (feet/year)



2003 Setback Factors (feet/year)



----- Erosion Rate Factor Transition Boundary
 Beach Fill Project > 300,000 cubic yards


Inlet Hazard Area

Photo: 2009 USDA NAIP

Vicinity Map



Map Scale: 1:20,000



Horizontal Datum: NC State Plane NAD 83 Feet

Setback Factors on this map represents long-term average annual erosion rates measured in feet per year. Shoreline segments that are accreting or have erosion rates less than two feet per year receive a setback factor value equal to two.

The information presented here is not predictive, nor does it reflect short-term erosion potential. This map may not be suitable for property specific determination of erosion rate factors near rate transition boundaries due to its small scale. For site specific determinations contact your CAMA Local Permit Official, or regional Division of Coastal Management field office.



400 Commerce Avenue
 Morehead City, North Carolina 28557
 1-888-4RCOAST

<http://www.nccoastalmanagement.net>


**FIGURE 1-2: 2011 Long-Term Average Annual Erosion Rates
 Eastern Holden Beach**



2011 Long-Term Average Annual Erosion Rate Update at Oak Island, North Carolina


Legend

2011 Setback Factors (feet/year)



----- Erosion Rate Factor Transition Boundary
 Beach Fill Project > 300,000 cubic yards

2003 Setback Factors (feet/year)




Inlet Hazard Area

Photo: 2009 USDA NAIP

Vicinity Map



Map Scale: 1:20,000



Horizontal Datum: NC State Plane NAD 83 Feet

Setback Factors on this map represents long-term average annual erosion rates measured in feet per year. Shoreline segments that are accreting or have erosion rates less than two feet per year receive a setback factor value equal to two.

The information presented here is not predictive, nor does it reflect short-term erosion potential. This map may not be suitable for property specific determination of erosion rate factors near rate transition boundaries due to its small scale. For site specific determinations contact your CAMA Local Permit Official, or regional Division of Coastal Management field office.



400 Commerce Avenue
 Morehead City, North Carolina 28557
 1-888-4RCOAST

<http://www.nccoastalmanagement.net>

**FIGURE 1-3: 2011 Long-Term Average Annual Erosion Rates
Western Oak Island**

2.0 PURPOSE AND NEED

The Town of Holden Beach proposes to construct a terminal groin on the shoreline adjacent to Lockwoods Folly Inlet that would complement the existing nourishment activities on the east end of Holden Beach. A beach nourishment component is also proposed and will occur concurrently with groin construction. *In general, the east end shoreline reach experiences localized erosion rates that are beyond the ability to effectively address with beach fill placement alone.*

The purpose of the proposed project is erosion control and beach/dune restoration which will protect residential structures and Town infrastructure on the east end of Holden Beach. In addition to homes and infrastructure, an additional purpose of the project is to maintain adequate recreational beach area as well as maintaining the public parking and public beach access on the eastern end of the island.



Figure 2-1: Holden Beach East End dune restoration activities following Hurricane Hanna dune erosion and breaching.

The east end of Holden Beach has and is experiencing consistent, relatively severe erosional conditions. The beach as well as the dune system have experienced chronic and episodic

erosion and have been rebuilt several times during the past decades. Likewise, dune breaching and flooding has also occurred, most recently during Hurricane Hanna in 2008 (see Figure 2-1). Note that periodic nourishments by both the Town and USACE have relieved this erosion; however, the periodic fill placement only provides a short-term benefit, and a more long-term solution is required.

The Town of Holden Beach desires to implement a long-term beach and dune stabilization strategy to protect the beach, dune system, and the public/private infrastructure by constructing a terminal groin at the eastern end of Holden Beach. In order to facilitate bypassing to downdrift areas, sand will also be placed adjacent to the groin. Final locations and placement quantities of sand will be determined during the project design process.

The proposed terminal groin installation is based on the following objectives:

- Stabilize the shoreline and maintain a healthy dry upper beach (berm) and dune;
- Increase opportunities for recreation, beach access, and enhancing available environmental habitats (i.e., potential to stabilize or increase inlet area shoreline sea turtle nesting, shorebird, and benthic community activity);
- Reduce future beach nourishment project frequency and required beach maintenance (dune rebuilding and revegetating, sand fending and walkover repair/replacement); and
- Optimize the groin benefits with reduction of both annual maintenance costs and future beach nourishment costs.

3.0 INDEPENDENT BEACH MANAGEMENT ACTIVITIES

In addition to seeking a permit for a terminal groin project, several other permitting projects are ongoing or planned by either the Town or the USACE. *Note that the proposed terminal groin project will include an east end nourishment.*

3.1 EXISTING TOWN BEACH NOURISHMENT PERMIT

Since 2002, Holden Beach has performed beach nourishment activities under CAMA Permit No. 14-02, NCDWQ Permit No. 20011836, and USACE Permits No. 200101101 and No. 200500935. The Town most recently modified its existing permits in early 2009 to allow a FEMA-sponsored nourishment to mitigate for Hurricane Hanna damages.

Given the above, the Town currently has active permits to place ~65,000 cy of beach compatible material utilizing the Smith and Turkey Trap upland borrow areas. Fill placement limits cover the majority of the Town's oceanfront shoreline. The DCM and USACE permits are valid until November 2013 and December 2014, respectively, and provide Holden Beach an active permit for emergency use following storm events. Volumes associated with such emergency activities are typically less than 100,000 cy (although the 2009 FEMA permit modification was 190,000 cy). Note that once an emergency nourishment is required, additional modifications to the permit pertaining to volume, placement, and possibly borrow sources may be necessary, depending on need at the time of the request. The Turkey Trap Road and Smith borrow sites are currently authorized sand sources in the existing permits (see Section 6.5 for more information on borrow areas).

3.2 ISLAND-WIDE NOURISHMENT UTILIZING OFFSHORE BORROW AREA

The Town is currently developing the necessary data/materials to submit a beach nourishment application using an offshore borrow area. The fill template for this project is centrally located on the island and separate from the terminal groin project.

There are essentially two reaches of beach that are historically nourished on Holden Beach:

- 1) Island-Wide (baseline Station 40+00 west to Station 270+00)
- 2) East End (Station 40+00 east to Lockwoods Folly Inlet)

Figure 3-1 presents these two reaches with Holden Beach and USACE beach fill placements since 2001. This document will refer to the "east end" as defined above. Also note that ATM observations indicate that the net transport between ~Stations 0+00 and ~40+00 (see Figure 3-




Figure 3-1:
Holden Beach Nourishment Activity Since 2001. Note only USACE projects occur on "East-End"
(HB=Holden Beach)

1 for stationing) is toward the east, due to the strong influence of the Lockwoods Folly Inlet processes (ATM, 2001).

Historically, the Town has not placed material on the east end beach and has relied on USACE shallow draft waterway maintenance dredging projects for east end sand placement. Note that the Town's nourishment projects are completely funded by the Town, from permitting through design, construction, and monitoring. The "USACE" east end beneficial nourishments from AIWW dredging, as described in this document, are primarily funded by the Corps, while the Town is typically responsible for 25 to 35% of the costs. The USACE is also in charge of permitting, design, construction and monitoring for the "USACE" projects described in this document. The 2001 beach nourishment along the central portion of Holden Beach ("Section 933 Project") was sponsored by the USACE, with cost sharing by the Town, as part of mitigation for deepening of the Wilmington Harbor.

Town fill placement is typically done in coordination with USACE east end fill placement. For example, in 2009 the Town began its "island-wide" fill placement where the USACE east end fill placement stopped (See Figure 3-1). Since 2002, the Town has not placed sand farther east than Station 40+00 (see Table 3-1) as a berm/beach nourishment. It is noted that the Town has performed limited *dune restoration efforts* on the east end in response to storm events.

Table 3-1: Town of Holden Beach Nourishment Summary over last decade (USACE fill placement is not included in this table).

Date	Baseline Stations Nourished	Approximate Volume of Material Placed (cubic yards)	Material Source
3/02 – 4/02	66+00 - 90+00, 175+00 – 217+00	141,700	Oyster Harbor upland site
Winter 2002-2003	90+00 – 175+00	30,000	Boyd Street Disposal Area
12/03 – 4/04	46+00 – 68+00 and 215+00 – 238+00	123,000	Smith borrow site
Early 2006	40+00-60+00	42,000	Smith borrow site
Early 2006	260+00 – 262+00	3,200	Smith borrow site
1/08 – 3/08	60+00 – 95+00 and 245+00 – 270+00	201,000	Smith borrow site
03/09 – 4/09	55+00 – 110+00 and 210+00 – 255+00	190,000	Smith borrow site

Regulatory agencies have historically established Station ~30+00 as the eastern-most limit of fill placement for Town projects. Natural resource agencies have promoted this to maintain a buffer for the shorebird habitat adjacent to Lockwoods Folly Inlet.

One of the primary goals of the Town's beach management strategy is to have no net reduction in sand volume from Holden Beach. Additional needs to increase storm protection to upland infrastructure, increase recreational beach area, and/or address hot spots may also be required.

For the proposed “island-wide” Holden Beach nourishment project utilizing an offshore borrow source, the forthcoming permit application is anticipated to include Stations 40+00 to 300+00, which represents the majority of the ocean shoreline (approximately 5.0 miles) with an average placed volume of 50 cy/ft (similar to the USACE Section 933 project). This equates to a volume of 1.3 million cubic yards, which would be broken down into manageable phases of work, similar to the original 2001 permits.

From a timing perspective, the Town must remain flexible in placement of beach fill material due to the ongoing consideration of a USACE “50-yr” nourishment project (see Section 3.3). The USACE 50-yr nourishment project is also essentially “island-wide”.

The ongoing USACE AIWW dredging and beach fill placement (e.g., beneficial use of dredged material) is an ‘east end’ project, similar to the proposed groin and nourishment project (see Section 5.3.3). While some coordination is needed to avoid possible overlap or logistical issues, “east end” projects are generally separate and unique from “island-wide” projects based on timing, purpose, and project sponsor(s).

3.3 USACE 50 YEAR PROJECT

The USACE Brunswick County Beaches (BCB) project includes the nourishment of Caswell Beach, Oak Island, and Holden Beach over a 50-year cycle. The USACE recently released an updated Review *Plan for the Integrated General Reevaluation Report and Environmental Impact Statement for Brunswick County Beaches, North Carolina* (USACE, 2011).

The 2011 Review Plan study area focus is Oak Island and Holden Beach. The two islands are separated by Lockwoods Folly Inlet. Other waterbodies in the study area include the Cape Fear River to the east, Shallotte Inlet to the west, and the Atlantic Intracoastal Waterway (AIWW) to the north. The study area also includes offshore borrow areas lying 1 to 8 miles from the shoreline and borrow areas in Jaybird Shoals, Frying Pan Shoals, Lockwoods Folly Inlet, and Shallotte Inlet.

The proposed nourishment footprint for Holden Beach will be an “island-wide” nourishment, similar in scope to the USACE’s 2001/2002 Section 933 project. The Oak Island nourishment is also planned to be island wide.

The current timeline for the BCB project estimates the Final EIS/NEPA Public Review (MSC Commanders Public Notice) in January 2014 (USACE, 2011). No dates for project construction (i.e. beach nourishment) are provided. Recent experience suggests that USACE nourishment projects are very susceptible to funding limitations, thus the fate of the BCB project is uncertain and not likely to advance to construction in the short-term.

4.0 PROJECT SITE HISTORY

The east end of Holden Beach has historically experienced severe erosional conditions. Many residences and infrastructure on the east end have been lost to erosion, where delineated parcels out in the water are all that remain (see Figure 4-1).




Figure 4-1: 1993 aerial and parcel lines depicting abandoned/destroyed parcels on East End of Holden Beach.

A temporary terminal groin field was constructed in the 1970s along the east end of Holden Beach. The project consisted of 15 sand-filled nylon tubes that were found to be beneficial in stabilizing dredged material from Lockwoods Folly Inlet (Machemehl, 1975). Figure 4-2 present a layout of the 15 groins on the east end of Holden Beach, and Figure 4-3 presents photos of the groins (from Machemehl, 1975). While the groin field was successful and economical, the temporary nature of the nylon material and the lack of ongoing nourishment activities limited its long-term effectiveness.





Figure 4-2: 1970's groin layout on east end of Holden Beach (source: Machemehl, 1975)



The USACE 1973 General Design Memorandum (GDM) for Yaupon and Long Beach also evaluated the use of terminal structures at Lockwoods Folly Inlet. Figure 4-4 presents a conceptual terminal groin system; although they are described as 'jetties' in the GDM (USACE, 1973). Sand management (i.e., mechanical back-passing and by-passing) was also included for this alternative.




Figure 4-4: Conceptual jetties alternative relative to sediment budget (USACE, 1973)

As previously mentioned, the east end area experiences localized erosion rates that are beyond the ability to effectively address with beach fill placement alone (again, recognizing the importance of inlet management to control the erosion along both sides of the inlet). In a February 2009 N.C. Coastal Resources Commission (CRC) meeting, Dr. Bill Cleary identified Lockwoods Folly Inlet as a good candidate for terminal groins. Additionally, the recent NC Terminal Groin Study (Moffatt & Nichol, 2010) included Lockwoods Folly Inlet as one of the 12 inlets studied statewide from an economics perspective.

5.0 EXISTING CONDITIONS

The primary cause of shoreline retreat along Holden Beach is due to long-term erosion through natural processes of littoral sediment transport, sea level rise, and storm related recession. Tidal currents, wave focusing and storage of sediment in the ebb and flood shoals of surrounding inlets (Shallotte and Lockwoods Folly) have also considerably affected the shoreline history of Holden Beach. Along the eastern end of the island, erosion has been prominent due to the continual shifting and reorientation of the main ebb and flood channel(s) of Lockwoods Folly Inlet. Figure 5-1 presents a typical schematic of these ebb and flood channel features.

Sediment transport along the shorelines adjacent to Lockwoods Folly Inlet has a net direction into the inlet, due to refraction of waves by the ebb shoal and inlet induced flood tidal currents. As a result, much of the sand on the inlet shorelines of Holden Beach and Long Beach (Oak Island) travels into Lockwoods Folly Inlet (especially during flood tides). During ebb tides, flow is more concentrated and jets out in a more centrally located flow, moving sediment near the main channel out onto the outer ebb shoal.



Figure 5-1: Conceptual regional and local net sediment transport schematic at Lockwoods Folly Inlet (2004 aerial).

In addition to inlet-related transport, the eastern end of Holden Beach is influenced by regional sediment transport. Regional net sediment transport is generally from north to south for the entire East Coast. Of course in the case of Holden Beach, sediment transport is not north to south, but east to west (i.e., downcoast). This is based on site observations and previous studies by the USACE (Thompson et al, 1999; USACE-CHL, 2008; OCTI, 2008). It is noted that some older references (USACE, 1973 and Machemehl, 1977) suggest that net transport along the eastern end of Holden Beach is more strongly toward the east. ATM observations indicate that the net transport between ~Stations 0+00 and 45+00 (see Figure 5-2 for stationing) is toward the east, due to the strong influence of the Lockwoods Folly Inlet processes (ATM, 2001). This varies based on shoal and channel configuration and wave climate.

On a regional level, sand transport occurs via “bypassing” of sand along the ebb shoal of the inlet (see Figure 5-1). The shoal system typically begins at the shoreline curvature inflection point on Long Beach and extends across Lockwoods Folly Inlet out to ~2,000 feet offshore, before arcing back to Holden Beach.




Figure 5-2: Current Inlet Hazard Areas for Lockwoods Folly Inlet. Holden Beach stationing is also pictured.

The overall east-west position of Lockwoods Folly Inlet has remained relatively stable for several centuries (Cleary, 2008). However, the position and orientation of the main ebb channel (large red arrow in Figure 5-1) relative to Holden and Long Beach significantly affects erosion

and accretion patterns at the east end of Holden Beach (and west end of Long Beach). Ebb shoal breaching (and associated sand bypassing across the outer ebb shoal bar(s)) and realignment events can be estimated using aerial photos and bathymetry (see Figure 5-3).

The western Oak Island shoreline, while affected by Lockwoods Folly Inlet, has been historically more stable than the east end of Holden Beach (Cleary, 2008). A similar pattern occurs at nearby Shallotte Inlet, where the west end of Holden Beach experiences typically less severe erosion cycles than the east end of Ocean Isle.

During a majority of the time over the past 70 years, the main ebb channel of the inlet has been aligned toward the southeast and Long Beach (see Figure 5-3, upper image). This has resulted in severe erosion along the east end of Holden Beach (some of the highest erosion rates in southeastern NC per OCTI, 2008) and resulted in the loss of properties along the beachfront. During times when the main ebb channel of the inlet is oriented closer to Holden Beach or perpendicular to the shoreline (as occurred in ~ 2001-2004, see Figure 5-3, lower image), some relief to the erosion occurs.

A critical consideration in stabilizing the east end of Holden Beach (and west end of Long Beach) is thus actively managing the inlet so that the channel is centered and oriented north-south to “equalize” the erosion stress on each side of the inlet and minimize sand losses from the beach. This is partially accomplished by the current periodic dredging of the inlet shallow draft channel areas by the USCAE, with placement of the sand on the adjacent beaches. *It is anticipated that a terminal groin, in conjunction with an ongoing inlet dredging/nearshore placement program, is the most effective solution to stabilizing the shoreline proximate to the inlet.*





Figure 5-3: USACE aerial photos showing erosion and accretion patterns related to position/orientation of inlet main ebb channel (aerials source: Cleary, 2008)

5.1 GROSS VERSUS NET SEDIMENT TRANSPORT

Terminal groins, as with all groins and jetties, typically hold sand on the updrift side (forming a 'fillet') while potentially detrimentally affecting downdrift beaches under extremely erosional conditions. In a regional net transport sense, Holden Beach is downdrift of the proposed eastern end terminal groin. However, locally, the inlet throat itself is downdrift of any groin placed along the inlet margin. Therefore, terminal groin design must consider the potential impacts, mainly to Holden Beach itself as well as Lockwoods Folly Inlet. Note that nourishment is proposed to be included with any groin installation. This minimizes potential for negative downdrift impacts. Additionally, combining beach fill and groin structures is typically more effective than nourishment-only in 'hot-spot' erosional areas.

Gross transport includes sand transport that moves both east to west and west to east, depending on wind and wave direction, currents, etc. Net transport sums up all gross transport and is typically used when describing sediment transport. Net transport has been estimated to be ~ 228,000 cy/yr to the west (Thompson, 1999). Gross transport is also important, especially for the east end of Holden Beach, where sand moving from west to east moves into Lockwoods Folly and is lost from the beach system into the shoals and channel. OCTI (2008) estimates gross transport to be ~650,000 cy/yr at Lockwoods Folly Inlet (~400,000 cy/yr to the west, ~150,000 cy/yr to the east; resulting in a net transport of ~250,000 to the west).

Sediment budget estimates for Lockwoods Folly Inlet (USACE, 1973; Machemehl, 1977; OCTI, 2008) indicate a "sink" of sand (material lost from the adjacent beaches and deposited into the inlet shoals) ranging from 125,000-240,000 cy/year (generated from both Holden and Long Beach shorelines). The proposed terminal groin would likely reduce the amount of sand lost to this "sink" effect. This would in turn reduce annual maintenance dredging costs.

5.2 NATURAL RESOURCES

The estuarine/back bay region of Lockwoods Folly Inlet includes the Atlantic Intracoastal Waterway (AIWW) as well as Lockwoods Folly River (see Figure 5-4). The Lockwoods Folly River is a relatively small tidal river with very low freshwater inflows (USACE, 1992).




Figure 5-4: Lockwoods Folly Inlet (source: USACE Shallow Draft Users Meeting Presentation).

In 2009, Brunswick County submitted a Water Resources Development Grant Application to dredge shoals from the Lockwoods Folly River to enhance flushing (see Figure 5-5). According to the grant application: “*Sediment deposition is believed to be responsible for alteration of the hydrology and the aquatic habitat of tidal creeks at the southern extent of the Lockwoods Folly River.*” Figure 5-5 below presents a land classification schematic of the area.




Figure 5-5: Lockwoods Folly River area land classifications (source: Brunswick County, 2009)

In addition to the above project, the USACE has also studied the Lockwoods Folly Inlet area for its ongoing 50-year Brunswick County Beaches nourishment program. Figure 5-6 below is from a USACE presentation related to environmental resources at the inlet. Additionally, several general essential fish habitat (EFH) concerns were identified and these include:

- (1) Loss of benthic foraging habitat for finfish and shrimp.
 - (a) Shrimping grounds around the shoals
- (2) Finfish
 - (a) Sandy shoal features are important juvenile finfish foraging habitat
 - (b) Larval Fish transport




Figure 5-6: Natural resources as identified during the USACE Brunswick County Beaches Project Permitting (source: USACE presentation at January 2009 Brunswick County Beaches PDT meeting)

5.3 **ECONOMICS**

The oceanfront beaches and adjacent properties on the east end of Holden Beach comprise a major social and economic resource for the Town of Holden Beach. Additionally, tourism has been Brunswick County's number one industry for decades (South Brunswick Magazine, <http://www.thesbm.com/brunswicktda>). In general, erosion of the east end of Holden Beach can result in a reduced tax base due to the loss of homes as well as reduced tourism due to restricted beach access and recreation. As indicated previously, annual maintenance dredging of the shallow draft project at Lockwoods Folly Inlet, as well as annual dredging of the Lockwoods Folly AIWW crossing are also anticipated to be reduced as a result of the proposed terminal groin project.

5.3.1 **RECREATION**

Public access to the eastern end of Holden Beach and Lockwoods Folly Inlet are a critical economic component to the Town. Popular activities include, but are not limited to, surf fishing, swimming, surfing, walking, shell hunting, sunbathing, bird watching, and boating. Currently, there are periods of significant loss of dry beach due to erosion, which limits many beach

activities to low-tide periods. The proposed groin and nourishment project would make the beach more accessible during the year, particularly during times of high tide. Cost-effective maintenance of a navigable shallow draft channel from the ocean to the AIWW is also a benefit to recreational sport fishing interests, who have the opportunity to utilize the Lockwoods Folly Inlet channel to seek safe refuge in the event of storms.

5.3.2 INFRASTRUCTURE

In addition to residential homes, principal elements of the town's infrastructure include the streets, utility lines, and public access parking areas owned and maintained by the Town. FEMA has helped cover damages that occurred during hurricanes; however the Town has to fund any repairs due to northeasters or other erosional events not declared a federal emergency.

The recently published Terminal Groin Report (Moffatt & Nichol, 2010) developed two different economic categories for a general assessment of terminal groin feasibility:

- 1) 30 Year Risk Area (YRA)
- 2) Imminent Risk Property (IRP)

The 30 year risk areas (YRAs) were defined by lines on aerial photo maps provided by the North Carolina Division of Coastal Management. The maps are based on aerial photos from 2003-2009. Any land existing seaward of the lines is assumed to be at risk in the next 30 years. These lines were agreed upon by the Science Panel for use in this assessment since they represent the best currently available data (see Moffatt & Nichol, 2010 for more information).

Imminent Risk Property (IRP) and infrastructure are located immediately adjacent to erosion control sandbags locations or between two nearby sandbag locations (Moffatt & Nichol, 2010).

The Terminal Groin Study included the following economic values:

- Residential property
- Commercial property
- Government property
- Road infrastructure
- Waterline infrastructure
- Sewer infrastructure
- Property tax base and revenues
- Recreation and environmental value

The NEPA permitting process for the proposed terminal groin project will build upon the economic analysis established in the Terminal Groin Study.

5.3.3 DREDGING

Lockwoods Folly Inlet contains a federally authorized shallow draft navigation channel where the USACE performs routine maintenance dredging for navigation using pipeline (i.e., cutterhead), split-hull hopper, and side-cast dredges. Due to different USACE funding sources, there are two basic routine maintenance activities that occur at Lockwoods Folly Inlet:

- 1) Outer Bar side-cast dredging
- 2) Lockwoods Folly Inlet AIWW crossing cutter-head dredging and beach fill placement

Figure 5-7 presents these two project footprints. In terms of outer bar dredging, there is no defined dredge template for Lockwoods Folly Inlet and dredging activities are restricted to follow “deep water”. This restriction limits the ability for the USACE to perform advanced dredging; consequently, dredging within Lockwoods Folly Inlet itself generally occurs 2 - 3 times per year. Several shipwrecks also exist at this inlet that must be avoided.

In addition to ocean-side inlet areas, the AIWW portion of Lockwoods Folly Inlet has proven to be a valuable source of beach compatible material. Lockwoods Folly Inlet AIWW crossing is dredged annually and beach fill is usually placed on the eastern end of Holden Beach. The primary purpose of this project is for AIWW maintenance, therefore the project footprint is necessarily limited to the AIWW and a bend widener. Table 5-1 below presents the history of this project over the last decade. A project is currently contracted for winter 2011/2012 (per email communication from Roger Bullock, USACE Navigation Branch).

Table 5-1: Recent Lockwoods Folly Inlet AIWW Crossing fill placement on the eastern end of Holden Beach

Date	Beach Stations Nourished	Approximate Volume of Material Placed (cubic yards)
3/02 - 4/02	20+00 – 30+00	32,000
9/04 – 11/04	15+00 – 40+00	113,230
May 2006	15+00 – 40+00	62,853
Winter 2008/2009	20+00 – 40+00	100,000
April 2010	20+00 – 55+00	140,000
February 2011	20+00 – 40+00	32,000
Winter 2011/2012	20+00 – 40+00	30,000 estimated*

*Note – estimate from USACE Navigation Branch




Figure 5-7:
Lockwood Folly Inlet USACE Dredging Activities
Two primary USACE activities occur -
1) Outer bar side-cast dredging and 2) AIWW cutterhead dredging and beach fill placment

The shoaling rate for Lockwoods Folly Inlet has been estimated between 125,000 cy/yr (OCTI, 2008) and 140,000 cy/yr (Machemehl, et al., 1977). From a terminal groin and beach nourishment perspective, it would be beneficial if the current AIWW dredge footprint were expanded to capture more of the material that is trapped in Lockwoods Folly Inlet.

The beneficial use of this dredged material by the USACE for beach placement is a critical component of an effective inlet management plan and this is planned to occur in the future. If the USACE discontinues this practice due to funding shortages, then Holden Beach plans to establish a Memorandum of Agreement to continue this placement (and has been in contact with the USACE about this).

It is anticipated that a terminal groin will incrementally reduce the amount of AIWW dredging and therefore reduce costs associated with this effort. Reduced shoaling of the AIWW is beneficial to recreational and commercial navigation. The Varnamtown shrimping fleet on the Lockwoods Folly River and recreational sportfishermen from the area marinas use this reach of the AIWW frequently. While the proposed terminal groin project is anticipated to enhance navigation for inner portions of the Lockwoods Folly Inlet and the AIWW; the proposed groin will not cut off the outer ebb shoal (as a jetty would) and not eliminate the need for maintenance dredging.

6.0 AVAILABLE ALTERNATIVES

An important component of the Work Plan is to identify available alternatives for the proposed project. Available alternatives, as identified by the NC Division of Coastal Management (DCM), to consider include:

1. No action/abandonment
2. Buyout/relocation
3. Beach nourishment without inlet relocation
4. Beach nourishment with inlet relocation
5. Sand borrow site analysis/selection

In order to evaluate each alternative, an economic analysis will also be incorporated.

6.1 NO ACTION

The No-Action alternative refers to performing no beach or inlet management activities. This alternative would allow erosion to continue and would result in the loss of additional property. Properties would likely be condemned and require removal where homes and infrastructure are impacted. This would result in tax revenue losses accumulated to Brunswick County and the Town of Holden Beach in addition to the substantial loss of property value to the individual property owners. The No Action alternative would also likely limit beach recreation and tourism due to reduced access and minimal available dry beach at higher tides.

6.2 THREATENED STRUCTURE RELOCATION

The threatened structure relocation or buyout program is an alternative that can be practical under certain circumstances. The recent relocation of the “Serendipity” house in Rodanthe is an example of a recent relocation.

In terms of buyout programs, the Heinz (2000) report found that:

A previous attempt to encourage removal and relocation of threatened structures—the Upton-Jones Program, which existed from 1987 to 1994—was suspended because of limited usage and unintended outcomes. A relocation program, if pursued, would have to be carefully designed to avoid the shortcomings of the Upton-Jones Program.

Additionally, a recent study of the beaches in the state of Delaware by Parsons and Powell weighs the cost of beach retreat against the cost of beach nourishment over the next 50 years. The study concluded that the cost of retreating from eroding coasts will be approximately four times the cost of renourishing the state’s beaches (Parsons and Powell, 2001).

In order to review this alternative for the east end of Holden Beach, relocation and buyouts will be assessed on a site specific basis. Some losses will occur under this alternative and these losses typically include the costs of property lost, costs of property that must be purchased to relocate a structure, and the costs of relocation. Most homes on the east end of Holden Beach are single-family residential properties. Commercial and multi-family properties typically cannot

be moved, and the loss of the property is not recoverable. Costs associated with relocation/buyout are typically estimated over 10 to 30 year time span, in order to gauge long-term effects. Note that limited lots are available on Holden Beach and relocated structures would no longer be located on the oceanfront.

6.3 BEACH NOURISHMENT WITHOUT INLET RELOCATION

The beach nourishment without inlet relocation alternative has been the status quo for the last decade. While beach erosion has been reduced under this alternative (in comparison with the 1990s where many homes and properties were lost), additional alternatives (such as the proposed terminal groin project) may prove to be more practicable. Storm related erosion as well as long-term erosion continues to make the east end of Holden Beach vulnerable under this alternative. Terminal groins (as well as groins in general) are typically employed in areas where beach erosion rates have been historically larger than practical to treat with fill alone. Figure 6-1 below presents a photo of a recent USACE AIWW dredge and beach nourishment project on the east end of Holden Beach.



Figure 6-1: April 2010 photograph of the USACE Lockwoods Folly Inlet AIWW Nourishment project. Note Town-funded dune planting in the foreground.

6.4 BEACH NOURISHMENT WITH INLET RELOCATION

The beach nourishment with inlet relocation alternative will also be considered during the NEPA permitting process. However, it is noted that the Lockwoods Folly Inlet has in general been positionally stable for the last century (Cleary, 2008). While inlet relocation has been successful for the Mason Inlet relocation project in 2001 as well as other inlets that are highly migratory, inlet relocation at Lockwoods Folly Inlet is not anticipated to be a cost-effective or necessary

solution for inlet management. Inlet main ebb channel orientation has a direct effect on erosion/accretion trends on the adjacent shorelines (see Sections 4 and 5). . The current inlet location is favorably positioned (Cleary, 2008), however erosion continues to threaten the eastern end of Holden Beach, while the western end of Oak Island has a low (2 ft/yr) DCM long-term erosion rate (see Figure 1-3). A portion of the inlet management plan may include recommendations for additional measures to maintain a favorable orientation/alignment the inlet's main ebb channel.

6.5 SAND BORROW SITE ANALYSIS/SELECTION

The Town of Holden Beach, as a part of its ongoing beach management program, has developed a list of potential borrow areas and preliminarily screened them. The 2009 Holden Beach Management Plan considered several borrow sources and these generally include: upland, inlet/AIWW dredged disposal areas, offshore, and Lockwood Folly Inlet. All borrow sites were evaluated for sediment quality and quantity as well as permitting and logistical requirements.

Upland and inlet/AIWW dredged disposal areas will be the primary focus for this analysis. Sand borrow site analysis will incorporate the latest DCM sediment criteria for beach compatibility. As previously mentioned, the ideal borrow source is the Lockwoods Folly Inlet AIWW project that is conducted by the USACE on an annual basis (see Section 5.3.3). Material from this activity is placed on the eastern end of Holden Beach and this activity is expected to continue. Other alternatives will also be identified by the Town in order to continue this basic operation. Borrow areas types in this analysis include:

Upland sources –

- Suitable for small projects (< 200,000 cy) and to supplement other larger fill projects
- Good for dune rebuilding and creation
- Sand color and grain size typically not as good as in-water sources
- Slow production rates and shorter life-cycles (every 1-3 years)
- Truck traffic and DOT/road maintenance issues
- Turkey Trap Road site and Smith site are currently permitted

Dredge Spoil Islands along the AIWW (i.e. CDFs) –

- Consist of layered material that would require separation of beach compatible and non-beach compatible material
- Reuse of this material would increase CDF disposal capacity and allow continued disposal operations

- Islands have become valuable for natural resources, recreation, and in some cases, development

Lockwoods Folly (LWF) Inlet –

- Currently not fully utilized/optimized because of side-casting operation and only following “deep-water” permit criteria
- USACE AIWW related navigation dredging has placed approximately 300,000 cy of material on the beach since 2002 (~ 45,000 cy/yr)
- USACE regional analysis supports placement of 156,000 cy/yr (625,000 cy every 4 years) from LWF ebb shoals on Holden Beach
- Critical to long-term beach and inlet management
- Channel alignment /orientation and shoaling patterns have been documented to cause problems to adjacent shorelines

Figure 6-2 presents a general location map of the borrow areas to be included in this analysis. Additional discussion on borrow area sources is provided below.

USACE Lockwoods Folly Inlet AIWW dredging

Ideally, the annual USACE navigation related nourishment of Lockwoods Folly Inlet AIWW Crossing can be used to fulfill the nourishment component of a terminal groin project at Holden Beach. This should help facilitate permitting because the annual USACE Lockwoods Folly Inlet AIWW Crossing dredging/nourishment project is already permitted. Additionally, the ongoing nature of the inlet dredging would also continue to provide benefits to the groin effectiveness and most likely satisfy any ongoing nourishment requirements for the groin. Of course, the Lockwoods Folly Inlet AIWW Crossing nourishment volumes may also be decreased with the installation of a terminal groin. Figure 6-3 presents the typical placement footprint of the USACE Lockwoods Folly Inlet AIWW dredged area. The USACE AIWW projects typically place between approximately 30,000 and 125,000 cy of beach compatible material annually (see Section 5.3.3 for more information).




Figure 6-2
Potential and Historic Upland Potential Borrow Areas (BAs)
and Confined Disposal Facilities (CDFs) for dredged material




Figure 6-3: Annual USACE Lockwoods Folly Inlet AIWW dredging and beach placement schematic. Placement typically occurs between Holden Beach Station 20+00 and Station 40+00.

In order for the Town of Holden Beach to permit a terminal groin, it is anticipated that the Town will need to develop a nourishment plan separate from the ongoing USACE east end nourishment in the event that the USACE AIWW dredging project does not continue. As a result, the Town will include its own borrow area plan for the proposed terminal groin project. The Town has already coordinated with the USACE Navigation Branch and the NCDENR Division of Water Resources (DWR) about establishing a Memorandum of Agreement whereby the Town would fund any AIWW dredging (and beneficial nourishment) if USACE future funding is insufficient.

USACE Lockwoods Folly Inlet Outer Channel Dredging

As described in Section 5.3.3, side-caster dredges are used by the USACE to maintain the outer navigation channel at Lockwoods Folly Inlet. However, the new USACE shallow draft split-hull hopper dredge (the Murden) is slated to slowly replace the sidecaster dredge (personal communication, Bob Keistler, USACE Navigation Branch, 2011). This would allow for nearshore placement of beach compatible material that is currently sidecast. This option will continue to be explored with the USACE as the transition from side-casting to hopper dredging the outer channel occurs. The Town, Oak Island, Brunswick County, and NCDENR DWR have

recently entered into an agreement with the USACE to provide \$450,000 to continue dredging of the navigation channel for the 2012 federal fiscal year (i.e., Oct 1, 2011 to Sept 30, 2012).

Upland Borrow Areas

The Town's use of upland borrow areas has proven valuable for recent nourishment projects and the Town plans to continue the use of upland borrow areas in the future. Fill projects utilizing upland borrow areas can be extremely valuable for unplanned/emergency mitigation efforts, such as the 2009 Holden Beach project in response to Hurricane Hanna. Additionally, truck haul projects do not involve the expensive mobilization/demobilization costs associated with offshore dredges and can occur much more quickly.

Potential negative aspects of upland borrow areas in the region include variations in sand color, practical volume limitations, and placement methods (i.e. trucking). Additionally, the N.C. Department of Transportation requires permitting and has the ability to shut down operations or require roadway mitigation.

Three potential upland borrow areas are described below.

6.5.1 TURKEY TRAP ROAD (PERMITTED)

The Turkey Trap Road Borrow Site is located near the intersection of Turkey Trap Road and Stanbury Road, and is an approximate 3.6 mile drive to the beach strand. The site is owned by the Town and covers 38 acres. In early 2005 ATM contracted with Engineering Consulting Services, Inc. (ECS) to collect 10 soil borings from within the site. The borings were driven to a depth of approximately 35-40 ft below grade. From these 10 borings, 40 composite samples were analyzed by ECS according to standard methods.

The Turkey Trap Rd Borrow site is expected to yield ~ 460,000 cy of material. Note that the Turkey Trap Road borrow area is also known as the Kirby Walter site in previous permitting documents. The site has the necessary permits from NCDENR, USACE, Brunswick County, and NCDOT (driveway permit).

6.5.2 SMITH BORROW SITE (PERMITTED)

The Smith site has been tested previously (borings were taken in 2002, 2007 and 2009) and used in previous years for the Town's beach nourishment (see Section 8.2). The material quality varies depending on location within the property, but has in general been found to be suitable. The Smith site is an approximate 4.0 mile haul distance from the beach strand. There are some limitations to the Smith site, due to the owner's development plans that dictate which areas are possible for excavation. The site has also been for sale for residential development and therefore may not be available for future use. For planning purposes, this site can only be relied upon as a short-term source, however potentially 200,000 cy of beach compatible

material could be obtained, and possibly more. Figure 6-4 presents a photo of the Smith Site during nourishment operations in 2009.



Figure 6-4: Smith Upland Borrow Area during 2009 Holden Beach Nourishment Project

6.5.3 TRIPP UPLAND SITE

Limited boring information as well as test pit observations indicates that the Tripp site contains potentially a large quantity of light colored beach quality sand. The Tripp site is an approximate 64 acre parcel located off Makatoka Rd in Supply, NC. The site is located west of HWY 17N and is approximately a 13 mile drive from the beach strand. Figure 6-5 presents a photo of a test pit at the Tripp site. In comparison to the existing permitted borrow sites; borings indicate that this site represents the best upland material in terms of color. A large pond has been excavated at this site previously and is approximately 55 ft deep, therefore a relatively large amount of material may be available. The site also has an existing mining permit (similar to the existing permitted borrow areas).



Figure 6-5: Tripp Site Test Pit

6.5.4 MONKS ISLAND

Monks Island is a currently inactive dredge spoil site located adjacent to the Atlantic Intracoastal Waterway, on the western end of Holden Beach. The island is long and narrow with roughly uniform topography. The western half of the island has been divided into 5 residential lots which are currently for sale. The eastern end is available for mining. The potential borrow area consists of about 10 acres of land up to an elevation of +20 ft NGVD (~mean sea level). Based on a site visit by ATM and Holden Beach personnel, the material contained within the existing dikes consists of fine to medium grained sand and may be suitable for placement on the beach. However, currently there are no available borings to quantify sediment quality and quantity.



Figure 6-6: Monks Island CDF

In 2010, the USACE raised the Monks Island perimeter dike/berm to increase capacity. According to USACE staff, the site consists of a layered mixture of beach compatible/non-compatible material and is constructed on a wetland base. Therefore, its potential use as a borrow area for beach nourishment is questionable, however it cannot be ruled out with current data. Figure 6-2 presents an image of this location.

6.5.5 SHEEP ISLAND

Sheep Island is a currently inactive dredge spoil site located adjacent to the AIWW north of Oak Island. Sheep Island is long and narrow; central portions of the island lie at elevations near or a few feet above sea level while topography peaks at either end where dikes have been constructed by the USACE to contain dredge spoil (see Figure 6-7 for site photo).

At the western end of the island, the spoil area covers approximately 4 acres and fill reaches a height of +20 ft NGVD. At the eastern end the spoil area covers approximately 28 acres and the fill reaches a height of +20 ft NGVD. Based on an ATM site visit in July 2009, the material contained within the dikes consists of fine to medium grain sand and may be suitable for placement on the beach. However, currently there are no available borings to quantify sediment quality and quantity.



Figure 6-7: Sheep Island confined disposal facility (CDF)

Similar to Monks Island, Sheep Island was formed by side-casting and pipelining dredged material onto wetlands decades ago (a practice which is no longer allowed). Therefore the base of Sheep Island consists of cohesive muddy sediment (i.e. wetland soil), while the material within the CDF consists of a layered mixture of compatible and non-compatible material.

As a result, its potential use as a borrow area for beach nourishment is questionable and would require additional geotechnical data collection.

6.6 TERMINAL GROIN AND BEACH NOURISHMENT

The beach nourishment and terminal groin alternative is the pending preferred alternative and is discussed in more detail in the next section.

7.0 PENDING PREFERRED ALTERNATIVE -TERMINAL GROIN & NOURISHMENT

The pending preferred alternative to the chronic erosion on the eastern end of Holden Beach features the construction of a terminal groin in conjunction with a beach nourishment and inlet management program. The two primary components of the project are described in greater detail in the following sections. Note that the designs presented below are conceptual in nature and will be finalized during the NEPA permitting process.

7.1 TERMINAL GROIN COMPONENT

Preliminary conceptual terminal groin alternative layouts have been developed based on shoreline movement and historic conditions on the east end of Holden Beach. The general design goals include: protection of public access; improvement of recreational beach area; enhancement of upper beach/dune habitat; stabilization of the east end of the beach (which represents the highest erosion rates on the island) from short-term and long-term fluctuations; and to reduce beach and AIWW dredging maintenance costs.

In general, the length of the terminal groin is dictated by the size of the inlet, the configuration of the end of the island, and the length of shoreline the groin is designed to stabilize. Two conceptual layouts were developed and are presented in Figures 7-1 and 7-2. It is noted that these groin alternatives are necessarily conceptual only and subject to further detailed evaluation, but present the general area where a terminal groin would be considered.

Groin Alternative 1 - This conceptual layout consists of a large terminal groin structure approximately 1,600 feet in length and is located immediately adjacent to Lockwoods Folly Inlet. This long structure is anticipated to create a large sand fillet and is positioned to close off the nearshore flood channel(s) that carries sand into the inlet throat and AIWW area, and straighten the shoreline to the west of it (see conceptual sand fillet on Figure 7-1). The groin is presented as a rubble-mound (i.e., rock) structure that also features a 'spur' which extends out perpendicularly near the base of the groin. A similar feature occurs on the Ft. Macon terminal groin as well as other terminal groins. This spur feature helps in maintaining a buffer between the groin and the Lockwoods Folly Inlet Channel. Otherwise, the channel may migrate directly adjacent to the terminal groin (see Kieslich, 1981). The groin profile will also be similar in profile to that of the Ft. Macon groin (i.e., crest height ~7 ft MLW, crest width ~10 ft, 2:1 side slopes).

For this groin alternative, additional analysis to estimate the potential impacts of trapping a large volume of sand from reaching the inlet (and its effect on the inlet sediment budget) must be completed. This analysis would be part of the inlet management plan required for terminal groin permitting.



FIGURE 7-1:
Conceptual Terminal Groin Alternative 1
East End, Holden Beach
2010 Depth Contours in feet NGVD (MHW=3 ft, MLW=-2 ft); 2008 Aerial




FIGURE 7-2:
Conceptual Terminal Groin Alternative 2
East End, Holden Beach
2010 Depth Contours in feet NGVD (MHW=3 ft, MLW=-2 ft); 2008 Aerial

Groin Alternative 2 - This conceptual layout consists of a terminal groin typically 400-600 feet in length and is located to the east of existing shorefront properties (~Station 15+00). The shorefront properties along the shoreline from Stations 20+00 to 45+00 remain the most vulnerable from an erosion/storm damage perspective. The dune in this area was breached during Hurricane Hanna landfall in 2008 and remains a vulnerability in the upper beach and dune system. A groin is anticipated to enhance the upper beach, which would help maintain and stabilize the dune system. The groin is conceptually presented as a rubble-mound (i.e., rock) structure with an asymmetric T-Head. The T-Head feature is included to enhance fillet formation of the beach fronting the eastern shoreline area, since a shorter groin in this location would be expected to have less of a stabilizing effect on the shoreline to the west than Alternative 1. T-Heads may also help to minimize formation of potential rip currents. Construction of this smaller groin would be expected to have a smaller impact on the sediment budget of the inlet than Alternative 1, but may result in some additional erosion along the inlet margin (~Station 0+00 to 10+00), and thus more detailed analysis is required to determine the proper dimensions and location to maximize effectiveness while minimizing adjacent impacts. A box is shown on Figure 7-2 to depict the general area where a smaller groin may be considered.

Figure 7-3 below presents a conceptual profile of the Alternative 2 terminal groin at Station 20+00. The groin crest is ~7 ft NGVD and the profile generally follows the slope of the shoreline (MHW=+3 ft NGVD, MLW=-2 ft NGVD). The groin will be low-profile to allow some sand bypassing. Note that the May 2011 Station 20+00 in Figure 7-3 captures a USACE LWF Inlet nourishment project. The proposed fill template would be similar to these ongoing projects.




Figure 7-3: Conceptual groin profile for alternative 2. Several Station 20+00 transects are plotted for reference. Note that the USACE recently placed material for the May 2011 transect.

7.2 BEACH FILL COMPONENT

SAND SOURCES

As with any groin or terminal groin permitting project, beach fill must also occur to minimize any potential downdrift impacts and to enhance the project area in general. The terminal groin will also in turn slow erosional losses of any placed fill material.

There are four primary potential sources of beach fill material that are available for the proposed terminal groin project:

1. USACE Lockwoods Folly Inlet AIWW dredging
2. USACE Lockwoods Folly Inlet outer channel dredging
3. Upland Borrow Areas
4. Upland Dredged Disposal Areas

These alternative sand sources are described in Section 5.5. Note that Holden Beach currently has an active permit for beach nourishment using an upland borrow area and is also currently developing a permit application for an offshore borrow area that is *independent of terminal groin permitting*.

BEACH FILL FOOTPRINT

As seen in the conceptual groin figures, a 'fillet' of sand is expected. In order to proactively create this 'fillet' feature, beach nourishment is required with groin construction. The beach fill essentially artificially creates this fillet feature and some overfill is also recommended to allow immediate bypassing of sand around the groin. The beach fill footprint is directly related to the size and configuration of the terminal groin. Because the terminal groin alternatives are conceptual, with a range in sizes provided, the beach fill footprints are also necessarily conceptual and a general range is provided.

The sand fillet volume of the proposed groin was calculated based on an area of sand accreting along the shoreline west of the proposed terminal groin. Minimum nourishment volumes can be computed by determining the cross-sectional area differences between the groin profile and the latest surveyed beach profile and then multiplying by the alongshore reach length. This is basically assuming that the updrift beach will match the groin profile. In order to arrive at a volume, total minimum beach nourishment equates to the minimum cy/ft multiplied by the alongshore reach length divided by 2 (for a triangular fillet).

In this way, a nourishment volume can be established for an individual groin. Note that this fill volume is rather small and it would not be cost effective to mob/demob a large ocean-going dredge for this amount. Note that fillet volume will change based on the latest shoreline position; with more volume needed for a more eroded condition.

Alternatively, timing groin construction with the annual USACE AIWW inlet crossing maintenance and/or shallow draft split-hull hopper inlet navigation dredging would likely provide adequate volumes (estimated fill at approximately 20 cy/ft) to prefill the groin fillet.

Recent nourishment projects by the Town have placed volumes from ~15 cy/ft to ~25 cy/ft utilizing upland borrow sources (see Figure 7-4). Additionally, recent USACE AIWW beach fills have ranged between ~20 and ~40 cy/ft. Fill templates for recent projects typically feature an upper beach berm with crest elevation of +7 ft NGVD. The constructed berm crest width typically ranges from 100 to 300 ft. A transitional slope of 1V:10H is typically constructed from the seaward berm crest to the pre-project beach. Figure 7-3 in the previous section displays a conceptual fill at Station 20+00 that ranges between 30 to 40 cy/ft (depending on the shoreline used).



Figure 7-4: 2009 Holden Beach Nourishment Project during Construction (West Reach is shown). Typical upland placement that will be employed for the proposed terminal groin project.

Benefits of nourishment and groin projects are often based on estimates of storm damage reduction for a prospective alternative (i.e., the level of damages prevented by implementation of an alternative). Figures 7-5 and 7-6 present conceptual beach fill footprints for the proposed project.

The Alternative 1 groin features a conceptual fill footprint of approximately 27 acres. Assuming 40 cy/ft unit fill placement, approximately 160,000 cy of material will be required.



FIGURE 7-5:
Conceptual Terminal Groin Alternative 1 with Beach Fill Footprint
East End, Holden Beach
2010 Depth Contours in feet NGVD (MHW=3 ft, MLW=-2 ft); 2008 Aerial




FIGURE 7-6:
Conceptual Terminal Groin Alternative 2 with Beach Fill Footprint
East End, Holden Beach
2010 Depth Contours in feet NGVD (MHW=3 ft, MLW=-2 ft); 2008 Aerial

The shorter Alternative 2 groin features a conceptual fill footprint of approximately 14 acres. Assuming a 30 cy/ft unit fill placement, approximately 80,000 cy of material will be required. Following initial project construction, on-going monitoring would determine future re-nourishment requirements.

Benefits

The implementation of the terminal groin in conjunction with beach nourishment is anticipated to widen the beach on a longer term basis. Studies in Florida (Dean, 1988) and North Carolina (Rogers, 2001) have shown that wider berm widths will cause waves to dissipate farther offshore and away from structures, thus reducing the breaking wave forces (and damages) on structures (see Figure 7-7).




Figure 7-7: Storm damage reduction adopted by Old Dominion after Dean, 1988. Damages were estimated from inspection of 540 structures damaged during Hurricane Eloise (1975).

7.3 CONSTRUCTION METHODS

The proposed terminal groin construction and beach nourishment will conceptually use land-based equipment (e.g. bulldozers, dumptrucks, excavators) to the extent possible. In general, excavators will load dump trucks at the borrow area, trucks will travel to the site and offload the beach-compatible sand, then a bulldozer will shape the sand into the design beach template. Alternately, a shallow draft cutterhead dredge may also be used, if the sand source is from Lockwoods Folly Inlet, the AIWW, or a nearby AIWW CDF. Sand would then be delivered via pipeline to the project site.

Construction materials for the groins (i.e., rock, geotextiles, and potentially marine mattresses for the foundation) will be delivered to the project site via trucks. In general, shorter groins would likely be constructed from land; however a longer groin may require construction of a trestle (similar to Amelia Island, FL terminal groin project) or the use of standard barges. In some cases, a jack-up barge may be required in the nearshore area to reduce impacts of waves and currents on construction operations. A small crane will place the rock and foundation materials. A track hoe or other excavator will also be required to excavate down to the base of the groin for foundation placement. Any sand temporarily displaced will be stockpiled and then used as backfill.

8.0 EXISTING AND PROPOSED DATA NEEDS AND STUDIES

Proposed terminal groin DCM regulations currently require:

- (1) Alternatives Analysis (including home/building relocation)
- (2) An Environmental Impact Statement (EIS) that has been developed by an independent third party
- (3) An engineering design bearing the seal of a registered professional engineer
- (4) Proof of notification of adjacent property owners and local governments on both sides of the inlet
- (5) An inlet management and monitoring (including mitigation triggers) plan
- (6) Identification of the financial resources necessary for potential future mitigation.

A significant amount of information currently exists on the Lockwoods Folly Inlet area. In addition to the reports and data included in the reference list, physical and biological reporting and monitoring data from all recent beach nourishment events, ranging from the USACE 2001 Wilmington Harbor Deepening nourishment project (Section 933 project) up to the Town's 2009 nourishment project can be used to develop baseline conditions and future monitoring programs.

An inlet management plan including consideration of the terminal groin project will be developed based on existing reports and data. From this study, a sediment budget will be developed based on the terminal groin and nourishment effects and a course of action (defining renourishment triggers, etc.) will be established based on ongoing and future monitoring. At this time, no numerical modeling is proposed. In general, the applicant does find numerical modeling to be a useful tool and the use of a suitable model can be explored in the future.

Available Studies

The Lockwoods Folly Inlet and the adjacent shorelines of Holden Beach and Oak Island have been studied from a shoreline change and sediment transport perspective since the 1970's, when the USACE evaluated shore protection for Brunswick County beaches and Machemehl placed 15 geotextile groins on the east end of Holden Beach. Since then, research and monitoring has continued. Please see the references in Section 10 for a listing of studies relevant to the permitting of a terminal groin on the east end of Holden Beach.

8.1 PROJECT TIMING

The Town of Holden Beach desires to have the ability to commence with project construction as soon as possible. From a timing perspective, project construction is anticipated to occur in the winter of 2013/2014 (i.e., approximately two years from now). This timing is obviously dependent on several other beach management activities as described in Section 3.

9.0 SUMMARY

The Town of Holden Beach has been actively and independently performing beach management activities on its shoreline for decades. More recently, the Town began performing several significant nourishment projects in order to augment and further the benefits of the USACE Wilmington Harbor Deepening 933 nourishment project in 2001/2002. The Town's projects are completely funded, permitted, designed, constructed, and monitored by Holden Beach.

From a beach nourishment and erosion perspective, the Town and the USACE have identified two general erosion control project reaches: 1) Island-Wide and 2) East-End. The "island-wide" reach ranges from Station ~40+00 to Station ~270+00 (~4.3 miles). The USACE 933 project and all Town nourishment projects over the last 10 years have occurred within the island-wide reach. These island-wide projects have been devoted to offsetting island-wide erosion and have been relatively successful in this endeavor.

The "east end" shoreline reach ranges from Lockwoods Folly Inlet to Station ~40+00 (~0.8 miles); where the island's highest erosion rates occur. The annual USACE Lockwoods Folly Inlet AIWW Crossing dredging and fill placement projects have a primary goal of offsetting inlet-related erosion on the east end of Holden Beach. The east end projects concentrate on a smaller shoreline area however this reach continues to be the most vulnerable to erosion and dune breaching (which occurred as recently as 2008 during Hurricane Hanna). Lockwoods Folly Inlet has been relatively stable historically with respect to its central channel location; however, the adjacent shorelines are characterized by some of the largest inlet-induced erosion rates in southeastern North Carolina (Cleary, 1999).

The Town would like to begin the NEPA permitting process for a terminal groin and nourishment project for the East-End of Holden Beach and the Work Plan described herein outlines and describes the proposed project (project site, purpose and need, existing studies, alternatives, etc.).

10.0 REFERENCES

- ATM, 2001. Holden Beach, NC beach Nourishment Project, Preliminary Design Report. Prepared for Town of Holden Beach, May 2001.
- ATM, 2009. Beach Management Planning and Borrow Area Investigation. Prepared for Town of Holden Beach, August 2009.
- ATM. Project Related Physical And Biological Monitoring Reports for Town Fill Projects constructed from 2002 thru 2009.
- Brunswick County. 2009. Water Resources Development Grant Application for the Lower Lockwoods Folly River Aquatic Habitat Restoration Project. Submitted to NCDENR DWR, July 1, 2009.
- Dean, R.G. 1988. Beach nourishment: theory and practice. Advanced Series on Ocean Engineering – Volume 18. World Scientific.
- Cleary, W. J., 1996, Lockwood's Folly Inlet: It's impact on the eastern margin of Holden Beach, NC, Unpublished report submitted to the Town of Holden Beach, 20p.
- Cleary, W., 2008. Overview of Oceanfront Shorelines: Cape Lookout to Sunset Beach, NC. Report prepared for Moffat & Nichol.
- Heinz. 2000. The Heinz Center Evaluation of Erosion Hazards. April 2000. <http://www.fema.gov/pdf/library/erosion.pdf>
- Kieslich, J. M. 1981. "Tidal inlet response to jetty construction," GITI Report 19, U.S. Army Engineer Waterways Experiment Station, Vicksburg, MS.
- Machemehl, J.L. 1975. Dredge Material Containment in Nylon Bags in the Construction of Mini-Projects for Beach Stabilization. Proceedings of the Eighth Dredging Seminar; Held November 8 1975, Houston, Texas. Sea Grant Report No. CDS-195, TAMU-SG-77-102, Texas A and M University, College Station, p 82-122, December 1976.
- Machemehl. 1975. Beach Erosion Control Project for Long Beach, NC. Report prepared for the Town of Long Beach, NC and the Department of Natural Resources and Community Development, State of North Carolina.
- Machemehl, Chambers and Bird. 1977. Flow Dynamics and Sediment Movement in Lockwoods Folly Inlet, North Carolina. UNC Sea Grant College Publication, UNC-SG-77-11.
- Machemehl, et al., 1977. An Engineering Evaluation of Low Cost Stabilization Projects in Brunswick County, NC. Coastal Sediments 1977.
- Moffatt and Nichol. 2005. Final report on costs, benefits, and management issues related to maintaining North Carolina's shallow draft navigation channels. Prepared for the North Carolina General Assembly
- Moffatt and Nichol. 2010. Final Report – Terminal Groin Study. Prepared for NC Coastal Resources Commission. March, 2010.

- OCTI (Offshore & Coastal Technologies, Inc.). 2008. Brunswick County Phase 1 Report. Prepared for the U.S. Army Engineer District, Wilmington, NC.
- Parsons, George R. and Michael Powell. "Measuring the Cost of Beach Retreat". Coastal Management, 29:91-103, 2001.
- Rogers, 2000. Beach Nourishment For Hurricane Protection: North Carolina Project Performance In Hurricanes Dennis And Floyd. National Beach Preservation Conference, Maui, HI Aug. 7-10, 2000 American Shore and Beach Preservation Association
- Thompson, E. F, Lin, L., and Jones, D.L. 1999. Wave Climate and Littoral Sediment Transport Potential, Cape Fear River Entrance and Smith Island to Ocean Isle Beach, North Carolina, U.S. Army Corps of Engineers, Engineer Research and Development Center, Technical Report CHL-99-18. Prepared for the U.S. Army Engineer District, Wilmington. 101 p.
- USACE, 1973. General Design Memorandum – Phase I; Hurricane Wave Protection – Beach Erosion Control; Brunswick County, NC, Beach Projects, Yaupon and Long Beach Segments."
- USACE (Miller). 1985. Beach Changes at Holden Beach, North Carolina, 1970-74. Report No. 83-5. USACE Coastal Engineering Research Center..
- USACE, 1992. Lockwoods Folly Numerical Circulation Study. USACE Waterways Experiment Station, Hydraulics Laboratory, 3909 Halls Ferry Road, Vicksburg, MS. Technical Report HL-92-2
- USACE. 1997. General reevaluation report for beach erosion control and hurricane wave protection, Brunswick County beaches, North Carolina, Ocean Isle beach portion. U.S. Army Corps of Engineers, Wilmington District, South Atlantic Division, 1997
- USACE-CHL, 2008. Memorandum for Record: Regional Analysis for Beach Nourishment Planning, Brunswick County, NC. Coastal and Hydraulics Laboratory, US Army Engineer Research and Development Center.
- USACE. 2011. Review Plan - Integrated General Reevaluation Report and Environmental Impact Statement for Brunswick County Beaches, North Carolina. October 2011
- USFWS. 2000. Brunswick County Beaches Project - Brunswick County, North Carolinadraft Fish And Wildlife Coordination Act Report. Prepared by: Howard F. Hall and Tracy M. Rice. Ecological Services Supervisor, U.S. Fish and Wildlife Service, Ecological Services Raleigh Field Office, Raleigh, North Carolina, August 2000
- Versar, Inc. 2004. Year 2 Recovery from impacts of beach nourishment on surf zone and nearshore fish and benthic resources on Bald Head Island, Caswell Beach, Oak Island, and Holden Beach, North Carolina, Prepared for U.S. Army Corps of Engineers, Wilmington District.

RESOLUTION 11-12
TERMINAL GROIN PERMIT APPLICATION

WHEREAS, the Town of Holden Beach, North Carolina is a barrier island bounded by the Atlantic Intracoastal Waterway to the north, the Atlantic Ocean to the South, the Shallotte Inlet to the West and the Lockwood Folly Inlet to the East; and,

WHEREAS, the Town of Holden Beach CAMA Land Use Plan supported the reconsideration of the previous state prohibition on erosion control structures particularly in inlet hazard areas; and,

WHEREAS, the Town of Holden Beach has supported by action and resolutions; all adopted unanimously, legislative efforts over the past several years to allow terminal groins in locations adjacent to NC inlets according to specific criteria and as determined by sound engineering practice; and,

WHEREAS, Senate Bill 110 "An Act To Authorize the Permitting And Construction Of Up To Four Terminal Groins Under Certain Conditions" has been enacted by the General Assembly; and,

WHEREAS, the Division of Coastal Management has presented the Terminal Groin Permit Process to the Coastal Resources Commission at their 25 August 2011 meeting; and,

WHEREAS, the Town of Holden Beach has a Beach Management Plan that identifies a terminal groin structure at the island's east end adjacent to the Lockwood Folly inlet as a solution that would help to stabilize the area; and,

WHEREAS, the Town of Holden believes it is in the best interest of its citizens, property owners, visitors, neighbors, mariners, commercial and recreational fisherman to stabilize the east end of Holden Beach adjacent to the Lockwood Folly Inlet; and,

WHEREAS, the Town of Holden Beach would like to move forward with obtaining the permits required to construct a Terminal Groin on the east end of Holden Beach.

NOW THEREFORE BE IT RESOLVED that the Board of Commissioners of the Town of Holden Beach NC does hereby direct the Holden Beach Town Manager to make application to the North Carolina Division of Coastal Management/Coastal Resources Commission for a permit to construct a Terminal Groin on the east end of Holden Beach adjacent to the Lockwood Folly Inlet.

This the 13th day of September, 2011.


J. Alan Holden, Mayor

ATTEST:


Heather Finnell, Town Clerk

